



Agri Power Plus 15W-40

Agricultural engine oil

Description

Castrol Agri Power Plus 15W-40 is a high performance engine oil designed for use in modern tractor engines.

Application

Castrol Agri Power Plus 15W-40 is recommended for use in diesel tractor and other farm machinery engines, both turbocharged and naturally aspirated. It is particularly recommended for mixed fleet farming operations covering most US, European and Japanese technology engines.

It is also suitable for use in a wide variety of engine types including diesel powered trucks and petrol powered cars and utility vehicles.

Advantages

Use benefits include:

- One oil for farm and on-road vehicles - reduces inventory
- Ideally suited for mixed fleet farming operations
- Improved soot related wear protection increases engine durability
- Excellent piston deposit control reduces oil consumption

Typical Characteristics

Name	Method	Units	Agri Power Plus 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.872
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	16.0
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	6350
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	120
Viscosity Index	ASTM D2270	None	141
Ash, Sulphated	ASTM D874	% wt	1.29
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.11
Pour Point	ASTM D97	°C	-36
Flash Point, COC	ASTM D92	°C	234

Product Performance Claims

ACEA E7
API CI-4/SL

Agri Power Plus 15W-40
18 Oct 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz